VENTHERMO · ECOSMART FIRE · OUTDOOR

# VERTIGO 40L

Venthermo technical summary, compiled from the official EcoSmart Fire European model page. This sheet accompanies the manufacturer’s installation and burner manuals.

| | |
|---|---|
| Dimensions | 1000 × 1000 × 340 mm |
| Weight | 59.54 kg |
| Materials — Surround | Fluid™ Concrete |
| Materials — Burner | Grade 304 Stainless Steel |
| Colours — Model | Natural, Graphite, Bone |
| Colours — Burner | Stainless Steel, Black |

## Bioethanol

| | |
|---|---|
| Burner | AB8 |
| Thermal output | 6 kW |
| Fuel capacity | 8 L |
| Burn time | 7–9 h |
| Fuel consumption | 1.1 L/h |
| Minimum indoor room volume | 116 m³ |

## LPG / Propane

| | |
|---|---|
| Burner | G16T |
| Thermal output | 19 kW |
| Burn time | 8–20 h |

## Natural gas

| | |
|---|---|
| Burner | G16T |
| Thermal output | 19 kW |

Gas configurations: outdoor only. Follow the official model and burner manuals for installation and operating clearances. Weights include the listed components. Output is converted from BTU/h and rounded to 0.1 kW.

Source: https://ecosmartfire.eu/fire-tables/vertigo-40l
Compiled: 16 September 2026 · Venthermo